printing these elements with different printing cylinders, and

periodically shifting one of said printing cylinders off from the web, each time for at least a duration of one turn of the printing cylinder.

2. (Amended) The method of claim 1, wherein the printed image comprises a number of subsequent panels, said panels having at least one element that is different from panel to panel, and wherein these elements are printed with a plurality of printing cylinders, and wherein:

said step of printing includes the step of printing at least one of said elements with each printing cylinder, and said step of periodically shifting includes the step of timing "on" and "off" adjustment movements of the printing cylinders such that each printing cylinder leaves those panels empty for which the elements are printed with another one of the printing cylinders.

- 3. (Amended) The method of claim 2, wherein the printed image has an element that is identically repeated for each panel, and said step of printing includes the step of printing this element with a separate printing cylinder which remains constantly in an "on" position.
 - 4. (Amended) The method of claim 1, further comprising the

A CONTRACTOR

step adjusting a plurality of printing cylinders "on" and "off" at timings that are offset in such a manner that an "on" adjustment of one printing cylinder occurs at a same longitudinal register as an "off" adjustment of another printing cylinder, so that the elements printed by these printing cylinders are in registry and form, in combination, an integral pattern.

5. (Amended) The method of claim 1:

wherein the step of printing includes the step of printing elements having a length of less than a peripheral length of the printing cylinder, as measured in a feed direction of the web, with a single printing cylinder, and

further comprising the step of timing "on" adjustments of this single printing cylinder such that the element printed thereby is inserted into the printed image in a predetermined position.

6. (Amended) The method of claim 4:

wherein the step of printing includes the step of printing elements having a length of less than a peripheral length of the printing cylinder, as measured in a feed direction of the web, with a single printing cylinder, and

further comprising the step of timing "on" adjustments of this single printing cylinder such that the element printed thereby is inserted into the printed image in a predetermined position.

- a plurality of printing cylinders,
- a feeding device for feeding a web to be printed,
- a shift mechanism for adjusting the printing cylinders individually on and off from said web, and
- a control unit adapted to control the shift mechanism for at least one of said plurality of cylinders such that this cylinder is periodically adjusted on an off from the web during the printing operation.
- 8. (Amended) The printing press of claim 7, wherein said shift mechanism is adapted to shift said at least one printing cylinder, that is adjusted on and off periodically, between an "on" position and an "off" position within a length of time that is substantially smaller than a rotation period of said printing cylinder.

Conf

LOCOCK, CSOKO